

Magnetic Assemblies >> Lifting Magnets

- Home
- Magnetic Assemblies**
 - Assembling Suspension
 - Pot Magnet
 - Magnetic stand
 - Magnetic Chuck
 - Magnetic Sweepers
 - Pull-and-Push Magnetic Attractor
 - Magnetic door suction
 - Magnetic Separator
 - Lifting Magnets
- Specification of Magnets
- Process Pieces
- Other Products

LMW-1 Lifting Magnets (Normal Temperature Tolerance)

We produce diverse kinds of lifting magnets in large quantities every year. Round or rectangular. Welded or cast. Land use or diving. Normal temperature tolerance or high temperature tolerance. Single or cascade. When you needs lifting magnet, please call us. You'll always hold a winning hand if you use Yuxiang lifting magnets!



Technical Specification Voltage Rated 200DC Working Duration(TD):60%

Model		LMW1-70	LMW1-90	LMW1-110	LMW1-130	LMW1-150	LMW1-165	LMW1-180	LMW1-185	LMW1-210	LMW1-240	
Outline Dimensions	A	700	900	1100	1300	1500	1650	1800	1850	2100	2400	
	B	840	1100	1150	250	1300	1500	1500	1550	1900	2000	
	C	160	190	210	240	340	340	360	360	400	450	
	D	100	120	140	170	200	200	220	220	250	280	
Weight	E	35	40	50	60	60	60	75	75	80	80	
		510	850	1400	2150	2850	3650	4600	5000	6700	8700	
Cool-State Current	A	16	26	35	53	71	80	102	108	125	150	
Power Consumption	kw	3.5	5.7	7.7	11.7	15.6	17.6	22.4	23.8	27.5	33	
Lifting Capability	Steel Spehere	2500	4500	6500	8500	11000	13000	14500	15500	21000	23000	
	Casting Iron(Cool/Hot)	400/210	620/420	1050/810	1450/1150	2000/1600	2400/1850	2800/2100	3100/2300	3600/2900	4900/4100	
	Steel Remainder (Cool/Hot)	400/210	620/420	1050/810	1450/1150	2000/1600	2200/1800	2800/2100	2900/2200	3600/2900	4100/3400	
	Scrap (Cool/Hot)	130/110	260/210	460/410	710/610	1000/850	1400/1200	1550/1300	1750/1500	2150/1800	2950/2350	
Auxiliary Device	Cable Spehere	DL-102					DL-202					
	Cable Roll	JTA50-15-2 II			JTA65-15-2 II		JTA80-15-2 II	JTA120-15-2 II		JTA150-15-2 II		
	Cable	10mm ²	2 cores		16mm ²	2 cores		25mm ²	2 cores		35mm ²	2 cores
		20m	1 piece		20m	1 piece		20m	1 piece	20m	1 piece	
	Rectifying Control Box	LA-5	LA-10		LA-15	LA-20		LA-25		LA-30	LA-35	

(For Reference Only)

Super-strong excitation, 290VDC for starting to lift, 200VDC for transporting.

[LWM-1 Lifting Magnets](#) | [Permanent Magnet Lifter](#)